







SOHORAID DR3-B31-B

1-Bay 2.5"/3.5" SATA III HDD/SSD & 2-Bay 2.5" SATA III HDD/ SSD Hardware RAID Storage

USB 3.1 Gen 2 Type C, Hot-Swappable Drive, Support RAID 1/JBOD mode

The DR3-B31-B supports USB3.1 Gen 2 Protocol together with JBOD/ RAID 1 storage modes which gives you an up to 10Gbps speed and a valuable storage mode choices. You could easily use it for searching data and editing your huge photo galleries directly from your Macbook Pro (USB-C) from its easy and friendly to use features. And also, you could definitely edit the 4K high resolution videos with no any uncomfortable delay.

Features

- 1. Support USB3.1 Gen 2 Protocol (10Gbps) together with Type-C connector.
- 2. Support 2+1 bays, mainly for you to use both of highspeed 2.5" SSD for efficiency and high-capacity 3.5" HDD for mass storage space.
- 3. Support the 2 2.5" bay with RAID 1 mode for data protection during writings, and the 1 3.5" bay for huge data storage capacity.
- 4. Support the transportable feature at both of 3.5" HDD and anyone of the two 2.5" SSDs/HDDs
- 5. Help data protection in case if anyone of the two 2.5" SSDs/HDDs is defect.
- 6. Support in-chassis overheat temperature monitoring and warning feature.











- A. HDD access light
- B. HDD enclosure handle
- C. HDD tray ejection
- D. HDD enclosure keyhole
- E. Key access opening
- F. Mute button
 - (2.5" Hard disk warning)
- G. System indicator
- H. Fan
- I. Power switch
- J. Power socket
- K. USB 3.1 port
- (GEN2 10Gbps)
- L. Fan speed switch
- M.Mute switch
 - (System temperature warning)
- N. Anti-theft cord slot

Technical Specification

DR3-B31-B	
Interface	USB 3.1 Gen 2 (up to 10 Gbps)
Compatible Drive	1 x 3.5"/2.5" SATA III HDD/SSD (up to 6 Gbps) 2 x 2.5" SATA III HDD/SSD (up to 6 Gbps) Support large volume up to 10TB
Certification	CE/FCC
Storage Mode	JBOD (for 3.5" x 1) - Independent Mode RAID 1 (for 2.5" x 1) - Safe Mode
Operating System Support	Windows 7 or above, OS X 10.10 or above
Cooling System	4 cm Low noise smart fan x 2
Electrical and Operating Requirements	 Line voltage: 100-240V AC Frequency: 50Hz to 60Hz, single phase Maximum continuous power: 60W Operating temperature: 32° to 104° F (0° to 40° C) Storage temperature: -4° to 116° F (-20° to 47° C) Relative humidity: 5% to 95% noncondensing
Size	102(H)×122(W)×245.6(L) mm
Product Code	DR3-B31-B EAN: 4713227440387 UPC: 884826504566
Carton	8 pcs per carton
Package Accessories	DR3-B31 / DR3-B31-B x 1 (with 3.5" / 2.5" removable drive tray enclosed x1 and 2.5" removable drive tray enclosed x 2) USB3.1 Cable x 1 (Type-C to Type-C) Cable x 1 (USB-IF Certified) AC Power Cable x 1 User Manual x 1 Screws & Keys



