

SR4-B32A Product Specifications

Model No	SR4-B32A
Host Interface	USB-A
Device Interface	USB-C
Device-Side USB	USB 3.2 Gen 2x2
Included Cable	USB-C to USB-A
Maximum Host Link Rate	Up to 10Gbps with compatible USB 3.2 Gen 2 USB-A hosts
Supported Drives	4 × 3.5" / 2.5" SATA III HDD/SSD
Host Compatibility	Systems with USB-A host ports; USB-C hosts require a separate USB-C to USB-C cable
RAID Modes	RAID 0, RAID 5, BIG, JBOD
OS Support	Windows 7 or later, macOS 10.10 or later, Linux
Cooling	80mm fan with High/Low speed switch
Chassis	Aluminum chassis with active cooling
Status and Protection	Power, drive activity, drive failure, rebuild progress, overheat/fan failure LED, buzzer alerts
Power Input	Internal 150W (AC 100–240V, 50–60Hz)
Dimensions (H × W × D)	166 × 124 × 210 mm
Certifications	CE / FCC
Packaging	10 pcs per carton
Included Accessories	1 × SR4-B32A enclosure 1 × USB-C to USB-A cable 1 × power cord 1 × accessory kit (drive screws, keys) 1 × quick installation guide