

SR4-BA32 Product Specifications

Model No	SR4-BA32
Host Compatibility	Systems with USB-C or USB-A host ports
Device Port	USB-C (USB 3.2 Gen 2x2)
Included Cables	1 x USB-C to USB-A 1 x USB-C to USB-C
Maximum Host Link Rate	Up to 20Gbps with compatible USB 3.2 Gen 2x2 USB-C hosts
Supported Drives	4 × 3.5" / 2.5" SATA III HDD/SSD
RAID Modes	RAID 0, RAID 5, BIG, JBOD
OS Support	Windows 7 or later, macOS 10.10 or later, Linux
Cooling	80mm fan with High/Low speed switch
Chassis	Aluminum chassis with active cooling
Status / Alerts	Power, drive activity, drive failure, rebuild progress, overheat/fan failure LED, buzzer alerts
Power Input	Internal 150W (AC 100–240V, 50–60Hz)
Dimensions (H × W × D)	166 × 124 × 210 mm
Certifications	CE / FCC
Packaging Included Accessories	4 pcs per carton 1 x SR4-BA32 enclosure 1 x USB-C to USB-C cable 1 x USB-C to USB-A cable 1 x power cord 1 x accessory kit (drive screws and keys) 1 x quick installation guide